



AIR FLOWS /M3/H	GBW15P	GBW22P	FUEL CONS. /L/H	GBW15P	GBW22P
EXHAUST	165	220	100% LOAD	3.6	5.3
COMBUSTION	65	87	75% LOAD	2.7	4.0
COOLING AIR	3075	3380	CAPACITY (L)	51	51

GSW	ENGINE	ALTERNATOR	WEIGHT (KG)
GBW15P	403C-15G	E1S13 M/4/13	472
GBW22P	404C-22G	E1S13 M/4/19	534

NOTE: GENERATING SET MUST BE LOCATED WITH, AT LEAST, ONE METER FREE SPACE AROUND FOR MAINTENANCE WORK  
 SURFACE OF COOLING AIR INTAKE LOUVERS MUST BE, AT LEAST, TWICE SURFACE OF COOLING AIR EXHAUST LOUVERS

GBW EXHAUST GRID: 530x630  
 INTAKE GRID: 585x655  
 EXHAUST SILENCER: 60mm diameter

2005	FECHA	NOMBRE	
Dibujado	26 Apr	JUG	
Comprobado			
Examinado			
ESCALA	RECOMMENDED INSTALLATION DIMENSIONS GENSET SOUNDPROOF PERKINS 403C-15G/404C-22G WATER COOLED GBW15P/22P MANUAL CONTROL PANEL		No PIGBW15P-22P_S00 Sustituye a Sustituido por