



REF. ADS **01.01**

ACCESSORIES | HYDRAULIC LIGHTING TOWER

Available only under request for PRAMAC Generating Sets of the range:
GBL22-30-42D, GBW30-45P, GSW15-22P, GSL22-30-42D

- Suitable for Rental and Public Works, shows and social acts.
- 6 x 1.500W quartz/iodine halogen lamps or 6 x 400W metal halide lamps.
- Connection of lamps by CE sockets.
- 200.000 lumen lighting capacity .
- Site trailer with 4 supporting feet.
- Electric engine, control devices and hydraulic system for lifting operations.
- Telescopic tower with an extension of 7,5 metres (max. 9m)
- Galvanized mobile unit (site trailer).



- Multi-Directional lighting system by quartz/iodine lamps (halogen type). Also available with metal halide lights.
- Interchangeable lamps by using the same support.
- Quartz/iodine lights: 6 x 1.500W (200.000 Lumen) lamps with **12 kVA** of consumption.
- Metal halide lights: 6 x 400W (192.000 Lumen) lamps with **3,7 kVA** of consumption.
- Protection degree IP55.



- Lighting supply by CE sockets. Check GBL, GSL and GSW Data Sheet for more details.
- IP45 panel as place to protect both tower and lighting circuit breaker protection.
- Hydraulic tower control by push buttons for an easy operation.
- Easy and quick connection between genset and lights by means of socket.
- Hook to roll the socket cable when it is not being used.
- Manual turning up to 355° degrees by means of flywheel.
- Mechanical block to avoid the tower turning when it is being used.
- Electric engine with protecting steel plate to operate the hydraulic devices.
- Dual safety control system.



- Telescopic tower with a maximum extension of 9 metres (recommended: 7,5m).
- Searchlights connection by retractile cable, inserted in a protective tube.
- Mechanical block for supporting feet positioning.
- Steel box for placement of lamps once they have been removed from the tower.
- FRAME: made of galvanized high quality steel for a maximum loading of 1.800kg.
- SITE TRAILER: made of galvanized high quality steel and complete with: 1 axle, 2 wheels, mudguards, eye hook, jockey wheel and 4 telescopic supporting feet for adjustable height and reduction of risks by overturning.



TECHNICAL CHARACTERISTICS NOT IMPEGNATIVE RESERVATION OF MODIFICATIONS FOR INNOVATION OF THE PRODUCT

TECHNICAL CHARACTERISTICS NOT IMPEGNATIVE RESERVATION OF MODIFICATIONS FOR INNOVATION OF THE PRODUCT



DIMENSIONS AND WEIGHT:		
	<u>Minimum Dimensions (transport)</u>	<u>Maximum Dimensions</u>
Length	4.800 mm	4.600 mm
Width	1.800 mm	2.690 mm
Height	2.250 mm	8.350 mm
Weight	882 kg	

Manual turning up to 355°

