



ENDRESS

Power Generators

ESE 506 HG-GT ES DUPLEX

Order No. **1135551**



Main features

Alternator type	DUPLEX
Max. Output 1~ [kVA/kW]	5.5/5.5
Continuous Power 1~ [kVA/kW]	5.0/5.0
Nominal voltage [V]	230
Nominal Current [A]	21,7
Power factor cos (phi)	1
Frequency [Hz]	50
Protection Class [IP]	54

Engine

Engine Type	HONDA GX390 / 11 HP
Design	1-cylinder 4-stroke OHV
Displacement [ccm]	389
Output 3000 rpm	6,4
Fuel	Petrol
Fuel tank capacity [l]	33
Fuel consumption @ 75% PRP [L/h]	2,1
Running time @ 75% PRP	15,7
Starting system	Electric starter
Sound power level LWA [db(A)]	97
Sound pressure level LPA (7 m) [db(A)]	72
Weight in kg ca.	111
Dimensions L x W x H [mm]	780 x 550 x 595
Shockproof sockets	2 x 230 V/16 A 1 x CEE 230 V/32 A

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2019-3-20

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de

